Henan Rentai Machinery Co., Ltd. | Suhe Center, Jinshui District, Zhengzhou City, Henan Province | WhatsApp +86 185 3097 6313

Belt Conveyor

Conveying & Feeding · Model: 400–1600

Belt conveyor used as the continuous link between production machines. High capacity, long conveying distance, stable operation and low noise.

Technical parameters

型号 Model	输送长度 Length (m)	功率 Power (kw)	输送速度 Speed (m/s)	输送量 Capacity (t/h)	
400型	≤12/2.2	12-20/2.2-4	20-25/3.5-7.5	1.25-2.0	30-60
500型	≤12/3	12-20/3-5.5	20-30/5-7.5	1.25-2.0	40-80
650型	≤12/4	12-20/4-5.5	20-30/5.5-11	1.25-2.0	80-120
800型	≤10/4	10-15/4-5.5	15-30/5.5-15	1.25-2.0	120-200
1000型	≤10/5.5	10-20/5.5-11	20-40/11-22	1.25-2.0	200-320
1200型	≤10/7.5	10-20/7.5-15	20-40/15-30	1.25-2.0	290-480
1400型	≤10/11	10-20/11-22	20-40/22-45	1.25-2.0	400-680
1600型	≤10/15	10-20/22-30	20-50/30-75	1.25-2.0	600-1080

Applicable materials

Coal

Applications

Mining, metallurgy, chemicals, building materials and hydroelectric construction.

Working principle

The belt moves by friction on driven pulleys and carries material continuously between machines.

Wear parts & materials

Not stated in source catalogue

> All figures above are reproduced from the Henan Rentai product catalogue and confirmed in the technical agreement before contract.

All rights reserved. — Henan Rentai Machinery Co., Ltd.. Specification sheets and guides on this page are generated from the published catalogue. Configuration is confirmed in the signed technical agreement.