Henan Rentai Machinery Co., Ltd. | Suhe Center, Jinshui District, Zhengzhou City, Henan Province | WhatsApp +86 185 3097 6313

Impact Crusher

Crushing Equipment · Model: PF-1007–PF-1320

Impact crusher for material up to 120–500 mm and compressive strength up to 320 MPa. High-chromium blow bars and a special impact liner suit hard-rock crushing.

Technical parameters

型号 Model	规格 Specification (mm)	进料口尺寸 Feed Inlet Size (mm)	最大进料边长 Max Feeding Size (mm)	处理能力 Processing Capacity (t/h)	功率 Power (kw)	重量 Weight (t)
PF-1007	1000×700	400×730	250	15-60	37-55	11
PF-1010	1000×1050	400×1080	300	50-90	55-75	14
PF-1210	1250×1050	400×1080	300	70-130	110-132	17
PF-1214	1250×1400	400×1430	300	90-180	132-160	22
PF-1315	1320×1500	860×1520	350	120-250	180-260	26
PF-1320	1320×2000	860×2030	500	160-350	300-375	30

Applicable materials

Limestone

Applications

Hard rock aggregate and mineral crushing.

Working principle

Material is struck by high-speed blow bars and thrown against impact liners for repeated size reduction.

Wear parts & materials

High-chromium blow bars and impact liners

> All figures above are reproduced from the Henan Rentai product catalogue and confirmed in the technical agreement before contract.

All rights reserved. — Henan Rentai Machinery Co., Ltd.. Specification sheets and guides on this page are generated from the published catalogue. Configuration is confirmed in the signed technical agreement.