RENTAI · INDUSTRIAL EQUIPMENT
Henan Rentai Machinery Co., Ltd. | Suhe Center, Jinshui District, Zhengzhou City, Henan Province | WhatsApp +86 185 3097 6313 | Email info@hnrentaitech.com

Jaw Crusher

Crushing Equipment · Model: PE-150×250–PEX-300×1300

Jaw crusher for primary and medium crushing of ore and large lump material. Compression is provided by a moving jaw and a fixed jaw.

Technical parameters

型号 Model	进料口尺寸 Feed Inlet Size(mm)	最大进料边长 Max Feeding Length (mm)	出料口尺寸 Products Outlet Size (mm)	处理能力 Processing Capacity (t/h)	偏心轴转速 Rotation Speed of the Eccentric Shaft(r/min)	电机功率 Motor Power (kw)	重量 Weight (t)	外部尺寸(长×宽×高) Dimensions(L×W×H) (mm)
PE-150×250	150×250	125	10-40	1-3	250	5.5	0.8	720×660×850
PE-200×300	200×300	180	15-50	2-6	260	7.5	1.2	910×750×990
PE-200×350	200×350	180	18-70	3-10	260	11	1.5	1000×870×990
PE-250×400	250×400	210	20-60	5-20	300	15	2.8	1300×1090×1270
PE-400×600	400×600	340	40-100	16-60	275	30	7	1730×1730×1630
PE-500×750	500×750	425	50-100	40-110	275	55	12	1980×2080×1870
PE-600×750	600×750	500	150-200	80-240	275	55	15.8	2070×2000×1920
PE-600×900	600×900	500	65-160	50-180	250	55	17	2190×2206×2300
PE-750×1060	750×1060	630	80-140	110-320	250	90-110	29	2660×2430×2800
PE-800×1060	800×1060	640	160-220	130-330	250	110	29.8	2710×2430×2800
PE-830×1060	830×1060	650	160-220	150-336	250	110	30.7	2740×2430×2800
PE-870×1060	870×1060	660	200-260	190-336	250	110	31.5	2810×2430×2800
PE-900×1060	900×1060	685	230-290	230-390	250	110	33	2870×2420×2940

型号 Model	进料口尺寸 Feed Inlet Size(mm)	最大进料边长 Max Feeding Length (mm)	出料口尺寸 Products Outlet Size (mm)	处理能力 Processing Capacity (t/h)	偏心轴转速 Rotation Speed of the Eccentric Shaft(r/min)	电机功率 Motor Power (kw)	重量 Weight (t)	外部尺寸(长×宽×高) Dimensions(L×W×H) (mm)
PE-900×1200	900×1200	750	95-165	220-450	200	110	52	3380×2870×3330
PE-1000×1200	1000×1200	850	195-265	315-500	200	110	55	3480×2876×3330
PE-1200×1500	1200×1500	1020	150-300	400-800	180	160	100.9	4200×3300×3500
PEX-150×750	150×750	120	18-48	8-25	320	15	3.8	1200×1530×1060
PEX-250×750	250×750	210	25-60	13-35	330	30	5.5	1380×1750×1540
PEX-250×1000	250×1000	210	25-60	16-52	330	30	7	1560×1950×1390
PEX-250×1200	250×1200	210	25-60	20-61	330	37	9.7	2140×1660×1500
PEX-300×1300	300×1300	250	20-90	16-105	300	55	15.6	2720×1950×1600

Applicable materials

Limestone

Applications

Quarry, mining and aggregate production.

Working principle

Material is compressed between a fixed jaw plate and a moving jaw plate and discharges through the adjustable bottom opening.

Wear parts & materials

Jaw plates and side liners

> All figures above are reproduced from the Henan Rentai product catalogue and confirmed in the technical agreement before contract.

All rights reserved. — Henan Rentai Machinery Co., Ltd.. Specification sheets and guides on this page are generated from the published catalogue. Configuration is confirmed in the signed technical agreement.