Henan Rentai Machinery Co., Ltd. | Suhe Center, Jinshui District, Zhengzhou City, Henan Province | WhatsApp +86 185 3097 6313

Rotary Screen

Screening Equipment · Model: GS1230–GS2030

Rotary screen consisting of an octagonal drum, frame, chute, reducer and motor. Rotating drum and screen meshes classify crushed stone.

Technical parameters

型号 Model	小时处理量 Capacity (m³/h)	外筒直径 Outer diameter (mm)	长度 Length (mm)	功率 Power (kw)	外形尺寸 Size (mm)
型号 Model	小时处理量 Capacity (m³/h)	外筒直径 Outer diameter (mm)	长度 Length (mm)	功率 Power (kw)	外形尺寸 Size (mm)
GS1230	20-50	φ1200	3000	3	3580×1590×1675
GS1530	40-80	φ1500	3000	5.5	3980×1790×1975
GS1830	80-150	φ1800	3000	7.5	4150×1870×2240
GS2030	130-200	φ2000	3000	11	4230×1950×2950

Applicable materials

Limestone

Applications

Sand and gravel classification.

Working principle

Crushed stone enters a rotating octagonal drum and is classified through successive screen meshes.

Wear parts & materials

Not stated in source catalogue

> All figures above are reproduced from the Henan Rentai product catalogue and confirmed in the technical agreement before contract.

All rights reserved. — Henan Rentai Machinery Co., Ltd.. Specification sheets and guides on this page are generated from the published catalogue. Configuration is confirmed in the signed technical agreement.